


Model 790 Part No. 401479

Water Vent Valve

- For removing air from convectors, baseboard and wall radiation
- Safety drain connection for discharging moisture
- Fitting and ferrule for $\frac{3}{16}$ " (4.8mm) OD tubing
- Telescopic siphon tube
- $\frac{1}{8}$ " NPT straight shank
- Maximum operating pressure 30 psig (2.1 bar)*
- Maximum pressure 30 psig (2.1 bar)



**Water Vent Valve
Model 790**




Model 791 Part No. 401482

Water Vent Valve

- For convectors and small mains
- Safety drain connection for discharging moisture
- Fitting and ferrule for $\frac{3}{16}$ " (4.8mm) OD tubing
- Telescopic siphon tube
- $\frac{1}{4}$ " NPT straight shank
- Maximum operating pressure 50 psig (3.5 bar)*
- Maximum pressure 50 psig (3.5 bar)



**Water Vent Valve
Model 791**




Model 792 Part No. 401494

High Pressure Water Vent Valve

- For releasing air from hot or cold water or glycol mains, hydronic heating and chilling systems, storage and processing tank filters, centrifugal pumps with specific gravity greater than 0.7
- Cast iron body and cover, stainless steel interior
- Maximum operating pressure 250 psig (17.3 bar)*
- Maximum hydrostatic pressure 350 psig (24.2 bar)
- Maximum temperature 300°F (149°C)



**High Pressure
Water Vent Valve
Model 792**



Model 792 Capacity			
Water Pressure psig (bar)		Air Discharge to Atmosphere cu. ft./min. (cu. m/min.)	
100	(6.9)	10	(.28)
150	(10.3)	15	(.42)
200	(13.8)	20	(.57)
250	(17.3)	25	(.70)

*Maximum pressure against which the vent can open.