

INNOFLUE® SINGLE WALL COMPONENTS

Vibration Isolation Boot with Clamps



High temperature silicone boot seals InnoFlue® SW Vent Lengths and Fittings to appliance flue outlet.

Nominal Diameter PVC to PP	Part #	Width	I.D
6" (160)	ISVIB06	2.4 (60)	6.3 (160)
8" (200)	ISVIB08	2.4 (60)	7.9 (200)
10" (250)	ISVIB10	2.4 (60)	9.8 (250)
12" (315)	ISVIB12	2.4 (60)	12.4 (315)


Increases & Reducers



Centric Increases

Transitions vent system to a larger diameter. Install in vertical orientation only. Additional configurations available upon request.

Nominal Diameter	Part #	Overall Length "A"	Effective Length "B"	Max O.D. "C"
2 2/3" (60/80)	ISIA0203	5.9 (150)	3.5 (89)	3.7 (95)
3 3/4" (80/110)	ISIA0304	5.7 (145)	3.2 (81)	5.0 (126)
4 5/8" (110/125)	ISIA0405	6.8 (173)	4.3 (110)	5.8 (146)
5 1/2" (125/160)	ISIA0506	7.2 (185)	4.3 (110)	7.3 (185)
6 1/8" (160/200)	ISIA0608	10.4 (265)	6.5 (165)	8.8 (224)
8 1/10" (200/250)	ISIA0810	11.6 (295)	7.7 (195)	10.8 (273)
10 1/12" (250/315)	ISIA1012	18.2 (463)	5.5 (141)	13.8 (351)



Eccentric Increase

Transitions vent system to a larger diameter. Install in horizontal or vertical orientation. Other size combinations available upon request.

Nominal Diameter	Part #	Overall Length "A"	Effective Length "B"	Max O.D. "C"
2 2/3" (60/80)	ISEI0203	5.3 (135)	3.1 (79)	3.8 (97)
3 3/4" (80/110)	ISEI0304	6.1 (156)	3.6 (91)	5.0 (128)