## 14FHK-S SERIES STANDARD FILTER HOUSING KIT


## **Application:**

- Agriculture
- Drip Irrigation / Greenhouses
- Point of Use (Under Sink / Taste & Odour)
- Recreational Vehicle
- Water Well
- Whole House Residential

## Specification:

- Threads conform to ANSI/ASME B1.20.1
- Max Pressure Rating: Blue125 PSI\*
- Temperature Rating: 39-125°F (4-52°C)
- Filter head comes with pressure relief button on inlet side
- Mounting bosses molded in head for installation with mounting bracket
- Housing kit comes complete with filter housing, 1 O-ring installed plus 1 replacement O-ring, mounting bracket & hardware, and filter bowl wrench
- Accepts industry standard cartridges (not included)
- \* If working pressure is consitently over 60 PSI a pressure regulator valve is recommended to extend the lifespan of the bowl

Material List						
Part Name	Material					
Filter Head	Black Polypropylene					
Filter Bowl	C = Clear Styrene-Acrylonitrile					
	B = Blue Polypropylene					
Button Assembly	Stainless Steel, NBR & ABS					
O-Ring	Nitrile Buna Rubber					
Wrench	Polypropylene					
Bracket	White Powder Coated Steel					
Hardware	Stainless Steel					





Dimensions											
Part No.	Inlet/Outlet B	Povd	Flow Rate Initial PSI @ GPM	W		L		L1		Weight	
		Bowl		inches	mm	inches	mm	inches	mm	grams	
14FHK-SB-0503	3/8" NPT	Blue	7 PSI @ 1 GPM *	5.14	130.60	6.85	174.10	6.24	158.50	1067	
14FHK-SB-1007	3/4" NPT	Blue	7 PSI @ 11 GPM *	5.14	130.60	11.81	300.00	10.87	276.00	1750	
14FHK-SC-1007	3/4" NPT	Clear	7 PSI @ 11 GPM *	5.14	130.60	11.81	300.00	10.87	276.00	1835	
14FHK-SC-1007SS**	3/4" NPT	Clear	7 PSI @ 11 GPM *	5.14	130.60	11.81	300.00	10.87	276.00	1835	
14FHK-SB-2007	3/4" NPT	Blue	7 PSI @ 11 GPM *	5.14	130.60	21.69	550.80	20.74	526.80	2250	
14FHK-SC-2007	3/4" NPT	Clear	7 PSI @ 11 GPM *	5.14	130.60	21.69	550.80	20.74	526.80	2375	

<sup>\*</sup> Actual flow rates and pressure drop will be determined based on cartridge selection and fluid viscosity.



25 Whaley Avenue, PO Box 310, Milverton, ON CANADA NOK 1M0 Tel: 800-561-3164

boshart.com ♦ blog.boshart.com

<sup>\*\*</sup> Filter head comes with 303 stainless steel thread inserts. Housing Kit is not certified to NSF.