

Elbows

1.1



**Viega ProPress 90° elbow
Smart Connect Technology**

- For use with ASTM B88 and B75 tubing
- Copper
- Press connection

Components
EPDM sealing elements

Model 2916

P1	P2	Wt [lb]	Quantity	Part No	DG
1/2	1/2	0.116	100	77317	8
3/4	3/4	0.173	100	77022	8
1	1	0.278	5	77027	8
1 1/4	1 1/4	0.364	5	77032	8
1 1/2	1 1/2	0.667	1	77037	8
2	2	1.059	1	77042	8



**Viega ProPress 90° elbow
Smart Connect Technology**

- For use with ASTM B88 and B75 tubing
- Copper
- Press connection

Components
EPDM sealing elements

Note
Must be installed with Viega ProPress XL-C rings and V2 actuator.

Model 0916XL

P1	P2	Wt [lb]	Quantity	Part No	DG
2 1/2	2 1/2	2.101	1	20623	8
3	3	3.031	1	20628	8
4	4	5.724	1	20633	8



**Viega ProPress 90° street elbow
Smart Connect Technology**

- For use with ASTM B88 and B75 tubing
- Copper
- Press connection, street

Components
EPDM sealing element

Model 2916.1

P	FTG (CTS)	Wt [lb]	Quantity	Part No	DG
1/2	1/2	0.104	10	77347	8
3/4	3/4	0.164	10	77052	8
1	1	0.265	5	77057	8
1 1/4	1 1/4	0.353	5	77062	8
1 1/2	1 1/2	0.644	1	77067	8
2	2	1.025	1	77072	8



**Viega ProPress 90° street elbow
Smart Connect Technology**

- For use with ASTM B88 and B75 tubing
- Copper
- Press connection, street

Components
EPDM sealing element

Note
Must be installed with Viega ProPress XL-C rings and V2 actuator.

Model 0916.1XL

P	FTG (CTS)	Wt [lb]	Quantity	Part No	DG
2 1/2	2 1/2	1.955	1	20638	8
3	3	2.861	1	20643	8
4	4	5.510	1	20648	8



**Viega ProPress 90° reducing elbow
Smart Connect Technology**

- For use with ASTM B88 and B75 tubing
- Copper
- Press connection

Components
EPDM sealing elements

Model 2916.3

P1	P2	Wt [lb]	Quantity	Part No	DG
3/4	1/2	0.160	15	77325	8
1	3/4	0.251	10	77330	8



**Viega ProPress 90° elbow
Smart Connect Technology
Zero Lead**

- For use with ASTM B88 and B75 tubing
- Bronze
- Press connection, female pipe thread

Components
EPDM sealing element

Model 2914.2ZL

P	FPT	Wt [lb]	Quantity	Part No	DG
1/2	3/8	0.136	5	79520	8
1/2	1/2	0.181	5	79525	8
1/2	3/4	0.243	5	79530	8
3/4	1/2	0.245	5	79535	8
3/4	3/4	0.299	5	79540	8
1	1/2	0.313	1	79545	8
1	1	0.463	1	79550	8
1 1/4	1 1/4	0.694	1	79560	8
1 1/2	1 1/2	0.961	1	79565	8
2	2	1.609	1	79570	8