

INNOFLUE® SINGLE WALL COMPONENTS

EPDM Gaskets


Standard gasket for 2" through 6" diameter InnoFlue® SW. Inserted into the female end of each part, the gaskets keep flue gases and condensates within the vent system.



Nominal Diameter	Part #
2" (60)	ISGE02
3" (80)	ISGE03
4" (110)	ISGE04
5" (125)	ISGE05
6" (160)	ISGE06
8" (200)	ISGE08
10" (250)	ISGE10
12" (315)	ISGE12

Connector Ring


Provides reinforcement at joints to support loads of up to 99 lbs (45Kg). 6" through 12" connector rings are available but not required per UL-1738 and ULC-S636.



Nominal Diameter	Part #	O.D. "A"
2" (60)	IAN502	3.2 (81)
3" (80)	IAN503	4.1 (103)
4" (110)	IAN504	5.3 (134)
5" (125)	IAN505	5.8 (148)
6" (160)	IAN506	7.5 (191)
8" (200)	IAN508	9.4 (239)

Air Intake

Place atop a concentric appliance flue outlet when exhausting flue gases through InnoFlue® SW or Flex and combustion air is supplied from within.



Nominal Diameter	Part #	Overall Height "A"	Max O.D. "B"
2"/4" (60/100)	IAAI0204	3.5 (88)	3.9 (100)
3"/5" (80/125)	IAAI0305	3.5 (88)	5.0 (126)
4"/6" (110/160)	IAAI0406	3.5 (88)	6.3 (160)

Centrocerin

A water based lubricant used to ease the assembly of InnoFlue® SW & Flex. Applied to both the gasket and male end.



Package Size	Part #
50 ml	IACE50