

## Vent Lengths

Single Wall 6" – 12"

		Rigid Vent Length			
		Rigid polypropylene vent lengths with dedicated male and female ends. Female ends contain internal gasket and male ends can be field cut and chamfered to desired length.			
Nominal Diameter	Part	Overall Length A	Effective Length B	Max O.D. C	
6" (160)	ISVL061	15.5 (345)	12 (305)	7.2 (183)	
6" (160)	ISVL062	27.5 (700)	24 (610)	7.2 (183)	
6" (160)	ISVL063	39.5 (1004)	36 (914)	7.2 (183)	
6" (160)	ISVL066	75.5 (1919)	72 (1829)	7.2 (183)	
6" (160)	ISVL0610	124.25 (3162)	120 (3048)	7.2 (183)	
8" (200)	ISVL081	16.00 (412)	12 (305)	8.8 (224)	
8" (200)	ISVL082	28.2 (716)	24 (610)	8.8 (224)	
8" (200)	ISVL083	40.2 (1021)	36 (914)	8.8 (224)	
8" (200)	ISVL086	76.2 (1935)	72 (1829)	8.8 (224)	
8" (200)	ISVL0810	124.5 (3162)	120 (3048)	8.8 (224)	
10" (250)	ISVL101	16.00 (410)	12 (305)	10.7 (272)	
10" (250)	ISVL102	28.2 (715)	24 (610)	10.7 (272)	
10" (250)	ISVL103	40.2 (1019)	36 (914)	10.7 (272)	
10" (250)	ISVL106	76.2 (1934)	72 (1829)	10.7 (272)	
10" (250)	ISVL1010	123.9 (3147)	120.0 (3048)	10.7 (242)	
12" (315)	ISVL122	36.7 (932)	24 (610)	13.8 (350)	
12" (315)	ISVL123	48.7 (1236)	36 (914)	13.8 (350)	
12" (315)	ISVL126	84.7 (2151)	72 (1829)	13.8 (350)	
12" (315)	ISVL129	120.6 (3063)	108.0 (2743)	13.8 (350)	

## Elbows and Tees

		15° Elbow			
		For offsets or changes the direction of the vent system.			
Nominal Diameter	Part	Centerline Offset A	Effective Length B	Max O.D. C	
6" (160)	ISEL0615	1.0 (25)	5.1 (130)	7.2 (183)	
10" (250)	ISEL1015	1.9 (48)	10.6 (269)	10.7 (272)	
12" (315)	ISEL1215	4.4 (112)	18.7 (475)	13.8 (350)	

		8" Zero Radius 15° Elbow				
		For offsets or changes in the direction of the vent system.				
Nominal Diameter	Part	Centerline Offset A	Effective Length B	Max O.D. C	Zeta Value	
8" (160)	ISELS0815	1.18 (30)	5.55 (232)	9.1 (232)	.10	