SPECIFICATIONS

Notes:

1. 4" FPT inlet/outlet with 4" plain end adapters, single inlet and triple outlet.
2. Unit weight - w/ cast iron covers: 376 lbs. (For wet weight add 2,310 lbs.)
3. Maximum operating temperature: 150º F continuous
4. Capacities - Liquid: 277 gal.
   Grease: 1,068 lbs. (146 gal.) @250 GPM
   Solids: 69 gal.
5. For gravity drainage applications only.
6. Do not use for pressure applications.
7. Cover placement allows full access to tank for proper maintenance.
8. Vent not required unless per local code.
9. Engineered inlet and outlet diffusers with inspection ports are removable to inspect / clean piping.
10. Integral air relief / Anti-siphon / Sampling access.
11. Adjustable cover adapters provide up to 4" of additional height.
12. Designed for below-grade, above-grade, indoor or outdoor installations.
13. Safety Star®, access restrictor built into each cover adapter, prevents accidental entry to tanks (450 lb rating).



TOP VIEW
(COVERS REMOVED FOR CLARITY)



ISOMETRIC VIEW

ENGINEER SPECIFICATION GUIDE

Schier Great Basin™ grease interceptor model # GB-250-250HF shall be lifetime guaranteed and made in USA of seamless, rotationally-molded polyethylene with minimum 3/8" uniform wall thickness. Interceptor shall be furnished for above or below-grade installation with adjustable cover adapters, Safety Star® access restrictor built into each cover adapter, and three outlet options. Interceptor flow rate shall be 250 GPM. Interceptor grease capacity shall be 1,068 lbs. Cover shall provide water/gas-tight seal and have minimum 16,000 lbs. load capacity.



SECTION A-A



END VIEW

SPECIFICATION SHEET

MODEL NUMBER:

GB-250-250HF

PART NUMBER: 4055-031-01

DESCRIPTION:
GB-250-250HF GREASE INTERCEPTOR 250 GPM, 4" INLET/OUTLET, H-20 RATED CAST IRON COVERS

DWG BY:	DATE:	REV:	ECO:
C.SINCLAIR	5/4/2022	-	-

SCHIER

6455 Woodland Dr
Shawnee, KS 66218
Tel: 913-951-3300
Fax: 913-951-3399
schierproducts.com