

## Accessories

Single Wall 6" – 12"



### Bird Screen PPs-UV

Fits inside InnoFlue® SW end pipes at terminations.


Nominal Diameter	Part
6" (160)	IASPP06



### Bird Screen SS

Fits inside InnoFlue® SW end pipes at terminations.


Nominal Diameter	Part
8" (200)	IASSS08
10" (250)	IASSS10
12" (315)	IASSS12



### 6" Spacers

Self-positioning spacers centers InnoFlue® SW in a chase/chimney/B-vent.


Nominal Diameter	Part	Max Width A	Min Width
6" (160)	IASP06	25.0 (635)	7 (186)



### 8", 10" and 12" Spacers

Self-positioning spacers centers InnoFlue® SW in a chase/chimney/B-vent.


Nominal Diameter	Part	Max Width A* (when bent)	Min Width
8" (200)	IASP08	27.6 (700)	9 (228)
10" (250)	IASP10	29.5 (750)	11 (276)
12" (315)	IASP12	32.1 (815)	13 (341)



### Flue Clamp

Secures ISAG and ISAGL appliance adaptors to appliance flue exhaust.

Nominal Diameter	Part	Height A	Max. I.D. B
6" (160)	IAFC06	1.0 (26)	8.3 (211)



### Connector Ring

Provides reinforcement at joints to support loads of up to 99 lbs (45Kg). 6" through 12" connector rings are available but not required per UL 1738 and ULC-S636.

Nominal Diameter	Part	O.D. A
6" (160)	IANS06	7.5 (191)
8" (200)	IANS08	9.4 (239)
10" (250)	IANS10	10.7 (271)
12" (315)	IANS12	14.9 (378.5)