

4550 Stainless Steel Ball Valve

## Feature


100# WSP / 1000# WOG Stainless Steel 1-Piece Body Reduced port Threaded end (ANSI B16.34) Reinforced PTFE seats Blow-out proof stem Locking handle MSS-SP-110



Pressure / Temperature rating				
1000# WOG	100 psi max. at 366 °F			

## Material


	Part	Material	Specification
1	Handle sleeve	Vinyl	-
2	Handle	Stainless Steel	A276 304
3	Locking device	Stainless Steel	A276 304
4	Handle nut	Stainless Steel	A276 304
5	Stem washer	Stainless Steel	A276 304
6	Washer	Stainless Steel	A276 304
7	Packing	PTFE	-
8	Washer	PTFE	-
9	Stem	Stainless Steel	A276 304
10	Gasket	PTFE	-
11	Seat retainer	Stainless Steel	A276 316
12	Ball	Stainless Steel	A276 316
13	Seat	PTFE	-
14	Body	Stainless Steel	A316 CF8M
15	Washer	Stainless Steel	A276 304



## **Dimension**, Weight

redwhitevalvecorp.com

Size	d	Е	н	L	Weight
	[in]	[in]	[in]	[in]	[lb]
1⁄4"	0.18	3.03	1.34	1.59	0.14
3/8"	0.27	3.34	1.39	1.89	0.28
1⁄2"	0.36	3.85	1.69	2.24	0.38
3⁄4"	0.49	3.85	1.90	2.32	0.64
1"	0.63	4.21	2.36	2.77	0.97
1¼"	0.78	4.21	2.42	3.05	1.56
11⁄2"	0.97	5.32	2.77	3.25	2.02
2"	1.26	5.63	3.27	3.91	3.00





MARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.