

**Qty. Description**

1 : UP 15-10 SU7P/TLC, 1 Comfort valve



Note! Product picture may differ from actual product

Product No.: [595916](#)

595916  
5700394894807  
5700394894807

**Technical:**

Rated flow: 3.17 US GPM  
Rated head: 2.661 ft  
Approvals: CUL, NSF, UPC

**Materials:**

Pump housing: Stainless steel  
ASTM A351-CF8  
Impeller: Composite  
PES+30% GF

**Installation:**

Maximum ambient temperature: 104 °F  
Amb. max at 80 dgr C liquid: 176 °F  
Maximum operating pressure: 145.04 psi  
Type of connection: NPT  
Pipe connection: 3/4" NPSM  
Pressure rating for connection: PN 10  
Port-to-port length: 5 1/8 in

**Liquid:**

Pumped liquid: Water  
Liquid temperature range: 35.6 .. 150.8 °F  
Selected liquid temperature: 140 °F  
Density: 61.35 lb/ft³

**Electrical data:**

Max. power input: 25 W  
Mains frequency: 60 Hz  
Rated voltage: 1 x 115 V  
Current in speed 3: 0.23 A  
Capacitor size - run: 2 µF/400 V  
Number of poles: 2  
Insulation class (IEC 85): F  
Built-in motor protection: CONTACT  
Cable type: Connecting cord with plug  
Type of cable plug: Nema 5-15P

**Others:**

Terminal box position: 9H  
Net weight: 5.07 lb  
Gross weight: 6.06 lb  
Country of origin: US  
Custom tariff no.: 8413.70.2005



Company name:


Created by:

Phone:

Date:

19/03/2024

Description	Value
<b>General information:</b>	
Product name:	UP 15-10 SU7P/TLC, 1 Comfort valve
Product No:	595916
EAN number:	5700394894807
<b>Technical:</b>	
Speed no:	1
Rated flow:	3.17 US GPM
Max flow:	6.16 US GPM
Rated head:	2.661 ft
Head max:	5.25 ft
Head max:	3.281 ft
Approvals:	CUL, NSF, UPC
<b>Materials:</b>	
Pump housing:	Stainless steel
Pump housing:	ASTM A351-CF8
Impeller:	Composite
Impeller:	PES+30% GF
<b>Installation:</b>	
Maximum ambient temperature:	104 °F
Amb. max at 80 dgr C liquid:	176 °F
Maximum operating pressure:	145.04 psi
Type of connection:	NPT
Pipe connection:	3/4" NPSM
Pressure rating for connection:	PN 10
Port-to-port length:	5 1/8 in
<b>Liquid:</b>	
Pumped liquid:	Water
Liquid temperature range:	35.6 .. 150.8 °F
Selected liquid temperature:	140 °F
Density:	61.35 lb/ft <sup>3</sup>
<b>Electrical data:</b>	
Max. power input:	25 W
Mains frequency:	60 Hz
Rated voltage:	1 x 115 V
Current in speed 3:	0.23 A
Capacitor size - run:	2 µF/400 V
Number of poles:	2
Insulation class (IEC 85):	F
Built-in motor protection:	CONTACT
Thermal protec:	INT.
Cable type:	Connecting cord with plug
Type of cable plug:	Nema 5-15P
<b>Others:</b>	
Terminal box position:	9H
Net weight:	5.07 lb
Gross weight:	6.06 lb
Country of origin:	US
Custom tariff no.:	8413.70.2005



Pumped liquid = Water  
Liquid temperature during operation = 140 °F  
Density = 61.35 lb/ft<sup>3</sup>

## 595916 UP 15-10 SU7P/TLC, 1 Comfort valve 60 Hz

