



“E” dimension includes exposed rod threads beyond bottom of the hex nut. Exposed rod thread dimension is equal to the diameter of the rod used.

Materials/Finishes	Plain Carbon Steel (11B)	Electro-Galvanized (11G)
	Hot-Dip Galvanized (11HDG)	T-304 Stainless (11SS)
	T-316 Stainless (11SX)	
Variants:	Pipe Gard (11PG) - Please contact factory for details.	
	Electro-Galvanized, Imported: 1/2" - 12" (11GI)	
	Electro-Galvanized, 3/16" thick Felt-Lined, Imported: 1/2" - 8" (11GIFL)	
	Hot-Dip Galvanized, Imported: 2"-3", 4"-6", 8"-12" (11HDGI)	
	Clevis Standard with Reduced Rod (11RR)	
Service:	Designed for the suspension of non-insulated, stationary pipe lines.	
Approvals:	U.L. - U.L.C. listed (sizes 2-1/2" - 8" excluding 7") and FM approved (3/4" - 2" galv only. 2-1/2" - 8" plain and galv.). Complies with Federal Specification WW-H-171-E (Type# 1), A-A-1192 A (Type# 1) and Manufacturers' Standardization Society MSS SP-58 and SP-69 (Type# 1). Approvals do not apply to 11RR.	
Ordering:	Specify figure number, material, finish type and pipe size. For 11RR, Specify figure number, material, finish type, pipe size and rod size.	
Notes:	For sizes 20" and larger a spacer sleeve is added over the cross bolt. Upper locknut must be tightened securely to assure proper hanger performance. Stainless steel hangers are recommended for applications where protection from a corrosive environment is required.	



PIPE SIZE	PIPE OD	MATERIAL SIZE		BOLT	A	B	C	E	F	WGT EACH (LBS)	MAX REC LOAD (LBS)
		TOP	BOTTOM								
1/2	0.840	13ga x 7/8	13ga x 7/8	1/4	3/8	1-11/16	2-1/16	5/16	7/16	0.18	730
3/4	1.050	13ga x 7/8	13ga x 7/8	1/4	3/8	1-11/16	2-9/16	1-5/16	7/16	0.18	730
1	1.315	13ga x 7/8	13ga x 7/8	1/4	3/8	2-1/16	2-11/16	1-1/4	5/8	0.22	730
1-1/4	1.660	13ga x 7/8	13ga x 7/8	1/4	3/8	2-1/2	3-3/16	1-11/16	7/8	0.26	730
1-1/2	1.900	12ga x 7/8	12ga x 7/8	1/4	3/8	2-7/8	3-11/16	2-1/16	1-1/16	0.34	730
2	2.375	12ga x 7/8	12ga x 7/8	1/4	3/8	3-5/16	4-7/16	2-1/2	1-1/4	0.38	730
2-1/2	2.875	9ga x 1-3/16	10ga x 1-3/16	5/16	1/2	4-1/2	5-7/8	3-3/8	1-15/16	0.86	1130
3	3.500	9ga x 1-3/16	10ga x 1-3/16	5/16	1/2	4-3/4	6-1/2	3-11/16	1-3/4	0.96	1130
3-1/2	4.000	8ga x 1-3/16	10ga x 1-3/16	5/16	1/2	5-7/8	7-15/16	4-13/16	2-9/16	1.14	1350
4	4.500	8ga x 1-3/16	10ga x 1-3/16	3/8	5/8	5-15/16	8-3/16	4-9/16	2-1/8	1.26	1430
5	5.563	4ga x 1-1/4	8ga x 1-1/4	1/2	5/8	5-11/16	8-7/16	4-5/16	1-7/16	2.04	1430
6	6.625	3ga x 1-1/2	8ga x 1-1/2	1/2	3/4	6-13/16	10-1/8	5-3/16	1-3/4	2.80	1940
7	7.625	3ga x 1-1/2	8ga x 1-1/2	1/2	3/4	7-13/16	11-5/8	6-3/16	2	3.24	2000
8	8.625	3ga x 1-3/4	8ga x 1-3/4	5/8	3/4	8-1/16	12-7/16	6-1/4	1-7/8	4.46	2000
10	10.750	3/8 x 1-3/4	3ga x 1-3/4	3/4	7/8	10	15-7/16	8	2-1/4	8.06	3600
12	12.750	3/8 x 2	3ga x 2	3/4	7/8	11-9/16	18	9-9/16	2-13/16	10.34	3800
14	14.000	1/2 x 2	1/4 x 2	7/8	1	12-9/16	19-9/16	10-9/16	2-9/16	14.80	4200
16	16.000	1/2 x 2-1/2	1/4 x 2-1/2	1	1	13-15/16	21-15/16	11-15/16	2-13/16	21.00	4600
18	18.000	1/2 x 2-1/2	1/4 x 2-1/2	1	1	16	25	13-7/8	3-3/4	24.40	4800
20	20.000	5/8 x 3	3/8 x 3	1-1/4	1-1/4	17-1/2	27-1/2	15-1/8	3-3/4	47.00	4800
24	24.000	5/8 x 3	3/8 x 3	1-1/4	1-1/4	19-3/4	31-3/4	17-3/8	4	54.00	4800
30	30.000	3/4 x 3	3/8 x 3	1-1/4	1-1/4	24-1/8	39-1/8	21-1/2	4-3/4	69.50	6000

PROJECT INFORMATION			APPROVAL STAMP	
Project:			Notes:	
Address:				
Contractor:				
Engineer:				
Date:				
Approved	Approved as Noted	Not Approved		