# 807-2 Small Diameter

APOLLOPRESS® Press End Copper 90° Street Elbow FTGxC (1/2" through 2")

# SUBMITTAL SHEET

# "Apollo" Flow Controls





Job Name:	
Job Location:	
Engineer:	
Contractor:	
Tag:	
PO#:	
Rep:	
Wholesale Dist.:	

## **DESCRIPTION**

The APOLLOPRESS® 807-2 Small Diameter Press 90° Street Elbow features a lead free dezincification resistant copper body and an EPDM o-ring. APOLLOPRESS® products are manufactured utilizing proven ASTM materials and standards. Proudly made in the USA.

## **FEATURES**

- · Lead Free Construction
- Ridgid® XL Press Tool Compatible
- · Leak Before Press® Technology
- · Made in USA

#### **APPROVALS**

- UPC, cUPC & IPC
- IAPMO PS 117-2016 & TIL MSE-13
- · NSF/ANSI 61 Water Quality
- NSF/ANSI 372 Lead Free

## **PERFORMANCE RATING**

- · Maximum Pressure: 300 psi
- Temperature Range: 32°F to 250°F depending on application

#### **APOLLOPRESS®**

- Small Diameter Sizes 1/2", 3/4", 1", 1-1/4" 1-1/2" & 2"
- Model 807-2, 90° Street Elbow


APOLLOPRESS® connectors are designed for direct mechanical connection to ASTM B88-Type K, L, and M copper tubing in the hard drawn condition. Press connectors are not suitable for steam or flammable gas service.

# STANDARD MATERIALS LIST

Body	UNS C12200 Copper					
0-Ring	EPDM					
Lubrication	Silicone, ANSI/NSF-61 Listed					

# **DIMENSIONS**

ITEM NO.	SIZE (IN.)	DIMENSIONS (IN.)								WEIGHT	
HEMINO.	SIZE (IN.)	Α	В	С	D	E	F	HEIGHT	WIDTH	DEPTH	(LB.)
10075566	1/2	1.8	2.38	0.76	0.73	0.97	1.91	2.38	1.8	0.95	0.11
10075568	3/4	2.37	2.82	0.93	1.01	1.06	2.2	2.82	2.37	1.24	0.21
10075046	1	2.87	3.56	0.92	1.4	1.13	2.81	3.56	2.87	1.49	0.31
10075072	1-1/4	3.64	3.85	1.09	1.87	1.19	2.97	3.85	3.64	1.75	0.43
10075074	1-1/2	4.14	4.4	1.31	2.02	1.36	3.34	4.4	4.14	2.11	0.72
10075076	2	5.17	5.48	1.59	2.52	1.65	4.21	5.48	5.17	2.56	1.06



\*LEAD FREE: The wetted surfaces of this product shall contain no more than 0.25% lead by weighted average. Complies with Federal Public Law III-380. ANSI 3rd party approved and listed.

