

807L-2 Large Diameter

APOLLOPRESS® Press End Copper 90°
Long Turn Street Elbow FTGxC (2-1/2" through 4")

SUBMITTAL SHEET

"Apollo" Flow Controls



| | |
|------------------|--|
| Job Name: | |
| Job Location: | |
| Engineer: | |
| Contractor: | |
| Tag: | |
| PO#: | |
| Rep: | |
| Wholesale Dist.: | |

DESCRIPTION

The APOLLOPRESS® 807L-2 Large Diameter Press 90° Long Turn Elbow features a lead free dezincification resistant copper body, a patented stainless-steel solid cross-section grab ring, a nylon separation ring and an EPDM o-ring. APOLLOPRESS® products are manufactured utilizing proven ASTM materials and standards. Proudly made in the USA.

FEATURES

- Lead Free Construction
- Leak Before Press® Technology
- Visual Element, Break Away Band (Pat# 9,532,451)
- Ridgid® XLC Press Tool Compatible
- Made in USA

PERFORMANCE RATING

- Maximum Pressure: 300 psi
- Temperature Range: 32°F to 250°F depending on application

APOLLOPRESS®

- Large Diameter Sizes 2-1/2" through 4"
- Model 807L-2, 90° Long Turn Street Elbow

STANDARD MATERIALS LIST

| | |
|-------------|------------------------------|
| Body | UNS C12200 Copper |
| Grab Ring | 316/304 Stainless Steel |
| Spacer Ring | Nylon 66 |
| O-Ring | EPDM |
| Lubrication | Silicone, ANSI/NSF-61 Listed |


APPROVALS

- UPC, cUPC & IPC
- IAPMO PS 117-2016 & TIL MSE-13
- NSF/ANSI 61 - Water Quality
- NSF/ANSI 372 - Lead Free

APOLLOPRESS® connectors are designed for direct mechanical connection to ASTM B88-Type K, L, and M copper tubing in the hard drawn condition. Press connectors are not suitable for steam or flammable gas service.

DIMENSIONS

| ITEM NO. | SIZE (IN.) | DIMENSIONS (IN.) | | | | | | | | | WEIGHT (LB.) |
|----------|------------|------------------|-------|-----|------|------|------|--------|-------|-------|--------------|
| | | A | B | C | D | E | F | HEIGHT | WIDTH | DEPTH | |
| 10062071 | 2-1/2 | 6.4 | 6.92 | 1.9 | 3.19 | 2.26 | 5.34 | 6.92 | 6.4 | 3.16 | 2.11 |
| 10062073 | 3 | 8.28 | 8.71 | 2.1 | 4.62 | 2.49 | 6.87 | 8.71 | 8.28 | 3.68 | 3.48 |
| 10062074 | 4 | 10.44 | 10.98 | 2.5 | 5.88 | 2.87 | 8.63 | 10.98 | 10.44 | 4.7 | 6.06 |



*LEAD FREE: The wetted surfaces of this product shall contain no more than 0.25% lead by weighted average. Complies with Federal Public Law III-380. ANSI 3rd party approved and listed.

Customer Service (704) 841-6000
www.apolloflowcontrols.com

This specification is provided for reference only. Conbraco Industries Inc. reserves the right to change any portion of this specification without notice and without incurring obligation to make such changes to Conbraco products previously or subsequently sold. Please visit apolloflowcontrols.com for the most current information.

