



BOSHART INDUSTRIES

Telephone: 1-519-595-4444 - Toll Free: 1-800-561-3164

Fax: 1-519-595-4380 - www.boshart.com

5-3

August 1/18

VALVE-IN-HEAD PACKAGE

APPLICATIONS

- Water Wells
- Agriculture / Green Houses
- Lab Equipment
- Food Processing / Service
- Recreational Vehicles
- Drip Irrigation
- Main Line Residential Water
- Photographic
- Vending Equipment

KIT INCLUDES:

- Blue reinforced polypropylene filter head
- On, Off and By Pass positions built into head
- Clear styrene-acrylonitrile bowl or Blue polypropylene bowl
- Blue polypropylene full circle filter wrench
- "U" Style mounting bracket with hardware
- Custom made NBR "O"-ring plus one extra replacement

Max. Operating Temp:
120°F (50°C)

Max. Operating Pressure:
125 PSI (880 kpa)

Utilizes industry standard
cartridge (not included)



HOUSING KIT

PART NO.	INLET/OUTLET	BOWL LENGTH	FLOW GPM	DIMENSIONS	SHIPPING WGT-lbs	QUANTITY CTN	QUANTITY CASE	LIST PRICE-A
14HK-V10C-07	3/4" FPT	10" Clear	1 - 10*	13.78" x 5.16"	3.7	1	12	63.22
14HK-V10C-07SS ◇	3/4" FPT	10" Clear	1 - 10*	13.78" x 5.16"	3.7	1	12	91.07
14HK-V10B-07	3/4" FPT	10" Blue	1 - 10*	13.78" x 5.16"	3.7	1	12	61.93

◇ Filter head is white polypropylene and comes with 304 stainless steel thread inserts

ACCESSORIES

PART NO.	DESCRIPTION	LIST PRICE-A
14A-MBU-01	"U" Style mounting bracket with hardware	5.58
14A-FWS-03	Blue full circle filter wrench	2.60
14A-ORS-03	NBR "O"-Ring	1.42

REPLACEMENT PARTS

PART NO.	DESCRIPTION	LIST PRICE-A
14PT-VH-07	Blue Head	29.71
14PT-VH-07SS	White Head c/w S.S. Inserts	61.27
14PT-SB-10C	Clear Bowl	21.35
14PT-SB-10B	Blue Bowl	18.01

DELUXE FILTER HOUSING PACKAGE

APPLICATIONS

- Water Wells
- Agriculture / Greenhouses
- Lab Equipment
- Food Processing / Service
- Recreational Vehicles
- Drip Irrigation
- Main Line Residential Water
- Photographic
- Vending Equipment

KIT INCLUDES:

- Black polypropylene filter head (c/w pressure relief button)
- Clear styrene-acrylonitrile bowl or Blue polypropylene bowl
- White polypropylene "C-type" filter wrench
- "L" Style white powder coated steel bracket with hardware
- AS568-242 NBR "O"-ring plus one extra replacement

Max. Operating Temp:
120°F (50°C)

Max. Operating Pressure:
125 PSI (880 kpa)

Utilizes industry standard
cartridge (not included)



HOUSING KIT

PART NO.	INLET/OUTLET	BOWL LENGTH	FLOW GPM	DIMENSIONS	SHIPPING WGT-lbs	QUANTITY CTN	QUANTITY CASE	LIST PRICE-A
14HK-D20C-07	3/4" FPT	20" Clear	1 - 25*	23.25" x 5.50"	6.4	1	6	96.55
14HK-D20B-07	3/4" FPT	20" Blue	1 - 25*	23.25" x 5.50"	6.4	1	6	72.41

ACCESSORIES

PART NO.	DESCRIPTION	LIST PRICE-A
14A-MBD-03	"L" Style white powder coated steel bracket with hardware	7.91
14A-FWD-03	White polypropylene "C-type" filter wrench	3.34
14A-ORD-242	AS568-242 NBR "O"-Ring	0.65

REPLACEMENT PARTS

PART NO.	DESCRIPTION	LIST PRICE-A
14PT-DH-07	Black Head	13.00
14PT-DB-10C	10" Clear Bowl	18.57
14PT-DB-10B	10" Blue Bowl	14.67
14PT-DB-20C	20" Clear Bowl	73.34
14PT-DB-20B	20" Blue Bowl	37.13

* Actual maximum flow rates vs. pressure drop will be determined based on cartridge selections and fluid viscosity.