

BOSHART INDUSTRIES

Telephone: 1-519-595-4444 - Toll Free: 1-800-561-3164

Fax: 1-519-595-4380 - www.boshart.com

GIANT HOUSING PACKAGE

APPLICATIONS

• Water Wells

Restaurants

• R.O. Systems

• Spas and Hot Tubs

• Food Processing

Milling Machines

Vending Machines

• EDM Machines (Water Based)

• Drip Irrigation

• Whole House

Institutions

 Agriculture • Industrial / Commercial

• Greenhouses

Plating

Max. Operating Temp: 120°F (50°C)

Max. Operating Pressure:

For 10" Bowl: 100 PSI (700 kpa) For 20" Bowl: 90 PSI (630 kpa)

> Utilizes industry standard cartridge (not included)



August 1/18

• Black polypropylene filter head (c/w pressure relief button)

• Clear styrene-acrylonitrile bowl or Blue polypropylene bowl

• Black polypropylene full circle filter wrench

• "L" Style white powder coated steel mounting bracket with hardware

• AS568-358 EPDM "O"-ring plus one extra replacement

HOUSING KIT

PART NO.	INLET/ OUTLET	BOWL LENGTH	FLOW GPM	DIMENSIONS	SHIPPING WGT-lbs	QUAI CTN	NTITY CASE	LIST PRICE-A
14HK-G10C-07	3/4" FPT	10" Clear	1 - 15*	14.05" × 7.28"	8.7	1		120.73
14HK-G10C-07	3/4" FF I	10" Clear	1 - 15.	14.05" X 7.26"	0.1	1	4	120.73
14HK-G10B-07	3/4" FPT	10" Blue	1 - 15*	14.05" × 7.28"	8.7	1	4	101.90
14HK-G10C-10	1" FPT	10" Clear	1 - 20*	14.05" × 7.28"	8.7	1	4	120.73
14HK-G10B-10	1" FPT	10" Blue	1 - 20*	14.05" × 7.28"	8.7	1	4	101.90
14HK-G10C-15	1-1/2" FPT	10" Clear	1 - 25*	14.05" × 7.28"	8.7	1	4	120.73
14HK-G10B-15	1-1/2" FPT	10" Blue	1 - 25*	14.05" × 7.28"	8.7	1	4	101.90
14HK-G20B-07	3/4" FPT	20" Blue	1 - 35*	24" × 7.28"	11.2	1	4	167.14
14HK-G20B-10	1" FPT	20" Blue	1 - 40*	24" × 7.28"	11.2	1	4	167.14
14HK-G20B-15	1-1/2" FPT	20" Blue	1 - 50*	24" × 7.28"	11.2	1	4	167.14

ACCESSORIES	}		REPLACEMEN	T PARTS	
PART NO.	DESCRIPTION	LIST PRICE-A	PART NO.	DESCRIPTION	LIST PRICE-A
14A-MBG-03	"L" -style white powder coated steel	32.47	14PT-GH-07	Black Head	37.13
	mounting bracket with hardware		14PT-GH-10	Black Head	37.13
14A-FWG-03	Black polypropylene full circle	8.91	14PT-GH-15	Black Head	37.13
	filter wrench		14PT-GB-10B	Blue Bowl	57.56
14A-GOR-358	AS568-358 EPDM "O"-ring	2.13	14PT-GB-10C	Clear Bowl	66.84
		•	14PT-GB-20B	Blue Bowl	123.47

GIANT HIGH TEMPERATURE HOUSINGS

APPLICATIONS

• Suitable for hot water / high pressure service. These glass reinforced nylon housings offer an economical, lightweight, high capacity alternative to metallic vessels. Their economical price allows you to install a preferred "duplex system" for totally uninterrupted flow in a wide variety of applications.

Vegetable Oils

• Hot Water / Liquids • Alcohols

Gasoline

• Salt Water Fisheries • Photographic

• Toluene / Xylene

Max. Operating Temp: 180°F (82°C) Max. Operating Pressure*: 100 PSI

Utilizes industry standard cartridge (not included)

FEATURES / CONSTRUCTION / RATINGS

• Head comes with dual 1" FPT and 1-1/2" FPT threads on both inlet and outlet connections,

high temperature heads are not available with pressure relief / bleed button

- Positive "stop" in black glass reinforced nylon head and bowl connecting threads prevents overtightening of filter bowl
- Securely retained "O"-ring ensures an effective seal between head and bowl, eliminating potential leaks due to accidental misplacement of "O"-ring
- Mounting bosses molded in head for available mounting bracket

-		-					
PART	INLET/	BOWL	FLOW	DIMENSIONS	SHIPPING	QTY	LIST
NO.	OUTLET	LENGTH	GPM		WGT-lbs	CASE	PRICE-A
14H-GHT10BK-1015	1" & 1-1/2" FPT	10" Black	1 - 20*	13.33" × 7.54"	5.88	1	730.74
14H_GHT20BK_1015	1" & 1-1/2" FPT	20" Black	1 _ 25*	23 71" > 7 54"	8 25	1	883 14

ACCESSORIES

ACCESSORIES		
PART NO.	DESCRIPTION	LIST PRICE-A
14A-MBG-03	"L" -style white powder coated steel mounting bracket with hardware	32.47
14A-GFW-01	Giant universal black plastic filter wrench	12.08
14A-GOR-01	B358 Buna-N replacement "O"-ring	2.08

^{*} Actual maximum flow rates vs. pressure drop will be determined based on cartridge selections and fluid viscosity.

Rev. 4.0 CDN