

**DRESSER™  
PIPELINE SOLUTIONS**

**For Hi-Temp  
Applications**

**STYLE 38 HI-TEMP COUPLINGS**



Max Temp: 1200°



Carded Glass  
Gasket



Steam

W-R#	Description	OD
2801489	½" IPS	[.84]
2801490	¾" IPS	[1.05]
2801492	1" IPS	[1.32]
2801494	1¼" IPS	[1.66]
2801496	1½" IPS	[1.90]
2801498	2" IPS	[2.38]
2801500	2½" IPS	[2.88]
2801502	3" IPS	[3.50]
2801503	3½" IPS	[4.00]
2801504	4" IPS	[4.50]
2801506	5" IPS	[5.563]
2801508	6" IPS	[6.63]
2801510	8" IPS	[8.63]
2801512	10" IPS	[10.75]
2801514	12" IPS	[12.75]

- Carded Fiberglass. Withstands temperatures to 1200°. Please note: the non-resilient characteristic of carded fiberglass gaskets can result in a non-leakproof seal.

**STYLE 90 HI-TEMP COUPLINGS**



Max Temp: 1200°



Carded Glass  
Gasket



Steam

W-R#	Description
2814402	½" Style 90 - Hi Temp
2814404	¾" Style 90 - Hi Temp
2814406	1" Style 90 - Hi Temp
2814408	1¼" Style 90 - Hi Temp
2814410	1½" Style 90 - Hi Temp
2814412	2" Style 90 - Hi Temp

- Carded Fiberglass. Withstands temperatures to 1200°. Please note: the non-resilient characteristic of carded fiberglass gaskets can result in a non-leakproof seal.