

E-Series Thermal Expansion Tanks

Model Number	Tank Size	Tank Weight	Connection Size (NPT)	Dimensions (LxWxH)	Acceptance Volume	Factory Precharge
E-FTT5	2.1 gal	4.7 lbs.	3/4"	12.5"x8"x8"	0.9 gal	40 psi
E-FTT12	4.8 gal	8 lbs.	3/4"	15"x11"x11"	3.2 gal	50 psi
E-FTT18	6.3 gal	10.4 lbs.	3/4"	16.75"x11.5"x11.5"	4.5 gal	50 psi

Material Description

ShellCarbon SteelConnectionStainless steelDiaphragmButylColorAlmond

Operating Conditions

Max. Operating Pressure	150 psi
Operating Temperature	200° F
Warranty	5 years

Dimensional Data

Model	Α	в	С
E-FTT5	12.5"	8"	3/4"
E-FTT12		11"	3/4"
E-FTT18	16.75"	11.5"	3/4"

Technical Features

- All tanks are NSF61 Certified
- MIG welding eliminates interior rough spots and sharp edges
- Each tank is factory leak tested to ensure tank integrity
- 150 psi max pressure rating
- 3 layer electrostatically applied coating provides a durable appliance grade finish
- Exclusive polypropylene liner eliminates internal corrosion
- · Protected precharge valve eliminates potential leak path

