


# STAINLESS STEEL FITTINGS | 304 & 316


- 304 / 316 Stainless Steel • 150# • Material Test Reports (MTR'S) Available • Stainless Steel Conforms to ASTM A312
- Dimensions & Ends Conform to ASTM A733 • Threads Conform to ASME B1.20.1 • Meets NSF / ANSI 372

## Stainless Steel 45° Elbow



PART #		SIZE	DESCRIPTION	DIMENSIONS (IN)			WEIGHT LBS	PACKAGING	
STAINLESS STEEL 304	STAINLESS STEEL 316			Ø1	Ø2	A		BX	CS
SS4FF0018	SS16FF0018	1/8"	SS 45° Elbow	0.63	0.55	0.75	0.07	50	600
SS4FF0014	SS16FF0014	1/4"	SS 45° Elbow	0.71	0.63	0.75	0.07	30	360
SS4FF0038	SS16FF0038	3/8"	SS 45° Elbow	0.89	0.77	0.75	0.10	75	300
SS4FF0012	SS16FF0012	1/2"	SS 45° Elbow	1.18	1.08	0.85	0.22	50	200
SS4FF0034	SS16FF0034	3/4"	SS 45° Elbow	1.38	1.30	0.91	0.29	40	120
SS4FF0100	SS16FF0100	1"	SS 45° Elbow	1.75	1.63	1.08	0.50	20	60
SS4FF0114	SS16FF0114	1-1/4"	SS 45° Elbow	2.05	1.93	1.26	0.64	20	40
SS4FF0112	SS16FF0112	1-1/2"	SS 45° Elbow	2.34	2.24	1.40	0.90	10	30
SS4FF0200	SS16FF0200	2"	SS 45° Elbow	2.83	2.70	1.67	1.28	12	24
SS4FF0212	SS16FF0212	2-1/2"	SS 45° Elbow	3.56	3.43	1.83	2.75	-	12
SS4FF0300	SS16FF0300	3"	SS 45° Elbow	4.21	4.04	2.09	3.85	-	10
SS4FF0400	SS16FF0400	4"	SS 45° Elbow	5.26	5.06	2.58	5.93	-	2

## Stainless Steel Coupling



PART #		SIZE	DESCRIPTION	DIMENSIONS (IN)					WEIGHT LBS	PACKAGING	
STAINLESS STEEL 304	STAINLESS STEEL 316			øA	øB	L	L1	C		BX	CS
SS4CPL018	SS16CPL018	1/8"	SS Coupling	0.33	0.55	0.79	0.31	0.04	0.04	70	840
SS4CPL014	SS16CPL014	1/4"	SS Coupling	0.44	0.73	1.06	0.39	0.05	0.08	40	480
SS4CPL038	SS16CPL038	3/8"	SS Coupling	0.56	0.85	1.10	0.43	0.05	0.10	40	480
SS4CPL012	SS16CPL012	1/2"	SS Coupling	0.69	1.05	1.40	0.57	0.06	0.19	60	240
SS4CPL034	SS16CPL034	3/4"	SS Coupling	0.90	1.25	1.48	0.59	0.06	0.25	50	150
SS4CPL100	SS16CPL100	1"	SS Coupling	1.13	1.56	1.65	0.67	0.07	0.41	25	100
SS4CPL114	SS16CPL114	1-1/4"	SS Coupling	1.46	1.91	1.89	0.83	0.07	0.61	16	64
SS4CPL112	SS16CPL112	1-1/2"	SS Coupling	1.70	2.17	1.89	0.83	0.07	0.71	18	36
SS4CPL200	SS16CPL200	2"	SS Coupling	2.17	2.62	2.20	0.94	0.07	1.00	12	24
SS4CPL212	SS16CPL212	2-1/2"	SS Coupling	2.60	3.33	2.56	1.18	0.10	2.48	8	16
SS4CPL300	SS16CPL300	3"	SS Coupling	3.21	3.96	2.80	1.22	0.10	3.20	-	12
SS4CPL400	SS16CPL400	4"	SS Coupling	4.21	5.10	3.27	1.42	0.10	5.93	3	6
SS4CPL600	-	6"	SS Coupling	6.32	7.09	3.94	1.46	0.11	9.47	-	2