

HRC - HD Pipe Roller Chair

Designed for Supporting Pipe in Horizontal Applications


- Maximum temperature 450°F
- Complies with Federal Specification A-A-1192A Type 44, WW-H-171-E
- Type 45, ANSI/MSS SP-69 and MSS SP-58 Type 44
- Non conductive, corrosion resistant Pipe Rollers for protection against severe weather conditions and moderate corrosive conditions such as marine atmospheres.

Sizes: 2" - 16" Material: Steel

Finish: Hot Dipped Galvanized

Approvals: Complies with ANSI/MSS SP-69 MSS SP-58 Type 44, A-A-1192A Type 44, WW-H-171-E Type45





ITEM	SIZE INCHES	MAX LOAD (LBS)	A	В	С	D	L	EA WEIGHT
HRSP-HD02	2"	600	1-5/8"	2-7/8"	1-1/4"	0.42"	4"	0.82
HRSP-HD03	3"	700	2-1/4"	3-3/4"	2"	0.42"	5"	1.4
HRSP-HD04	4"	750	2-3/4"	4-3/4"	2"	0.54"	6"	2.64
HRSP-HD05	5"	750	3-1/2"	5-3/4"	3"	0.54"	8"	3.02
HRSP-HD06	6"	1,070	4"	6-7/8"	3-1/8"	0.54"	9"	5.29
HRSP-HD08	8"	1,350	5-1/8"	8-7/8"	3-3/8"	0.67"	12"	7.58
HRSP-HD10	10"	1,730	6-3/8"	11"	5-1/4"	0.67"	14-1/2"	13
HRSP-HD12	12"	2,400	7-1/2"	12-1/2"	5-1/2"	0.67"	16-1/2"	19
HRSP-HD14	14"	3,130	8-3/8"	14-3/8"	6-1/2"	0.67"	18"	28.04
HRSP-HD16	16"	3,970	9-1/2"	16-3/8"	8-1/4"	0.67"	20-1/2"	37.61

Engineer's Approval						
Job Name / #	Contractor	Date				
Job Location	Engineer	Date				