




Our larger capacity system allows optimal configurations of ductless indoor and outdoor units up to 17 SEER. Designed with cost-effectiveness in mind, Haier FlexFit ductless systems provide a solution to the most demanding comfort needs.


## Key Features

**DC INVERTER**

**A-PAM DC INVERTER**  
Latest high efficiency DC inverter technology



**-4°F HEATING**  
Low ambient heating down to -4°F (-20°C)



**3-D AIR FLOW**

Delivers air vertically and horizontally for even distribution throughout the room



**EASY INSTALLATION CLIP**

Built-in bracket allows more room to install and service



**BLUE FIN**

A hydrophilic aluminum fin, ensures condensing water flows smoothly



**QUIET MODE**

Minimizes indoor noise while maintaining comfort levels



**WARM START**

Ensures the fan will not blow cold air during heating mode startup



**2-WAY PIPING DRAIN**

Right or left side drain configuration simplifies installation



**TURBO MODE**

Cools or heats the room quickly



**AUTO LOUVER**

Adjusts airflow upward when cooling, or downward when heating



**LONG DISTANCE AIR SUPPLY**

Optimized fan motor and blower design enables up to 60 feet of air flow



**CHILD LOCK**

Prevents unintended and unsupervised use



**OPTIONAL WIRED REMOTE CONTROLLER**

Attractive wall-mounted unit is easy to use and features a large LCD display.



**SELF-DIAGNOSIS**

A PCB simplifies service and maintenance by displaying important operating parameters.



# Single Zone Systems

Haier


## Specifications



**Compressor Type:**  
DC Inverter Driven  
Rotary

**Voltage/Cycle/Phase:**  
208-230/60/1

**Operating Range (°F):**



**WIFI**  
Adaptable with  
WIFI Adapter (QAWF01A)

	Highwall		High Static Duct			Large Cassette			
<b>Outdoor Unit</b>	<b>1U24LP2VHA</b>	<b>1U36LP2VHA</b>	<b>1U24LP2VHA</b>	<b>1U36LP2VHA</b>	<b>1U48LP2VHA</b>	<b>1U24LP2VHA</b>	<b>1U36LP2VHA</b>	<b>1U48LP2VHA</b>	
UPC	6-88057-40802-6	6-88057-40803-3	6-88057-40802-6	6-88057-40803-3	6-88057-40805-7	6-88057-40802-6	6-88057-40803-3	6-88057-40805-7	
<b>Indoor Unit</b>	<b>AW24LP2VHA</b>	<b>AW36LP2VHA</b>	<b>AM24LP2VHA</b>	<b>AM36LP2VHA</b>	<b>AM48LP2VHA</b>	<b>AL24LP2VHA</b>	<b>AL36LP2VHA</b>	<b>AL48LP2VHA</b>	
UPC	6-88057-40806-4	6-88057-40807-1	6-88057-40808-8	6-88057-40809-5	6-88057-40811-8	6-88057-40812-5	6-88057-40813-2	6-88057-40815-6	
<b>Cooling</b>	Rated Capacity Btu/hr	24,000	35,000	24,000	35,000	45,000	24,000	35,000	45,000
	Capacity Range Btu/hr	6,800 - 30,700	8,500 - 37,500	6,800 - 30,700	8,500 - 37,500	11,900 - 54,500	6,800 - 27,000	8,500 - 37,500	11,900 - 52,800
	SEER/EER	17/10	17/8.6	17/11	17/10	16.9/10	17/11.5	17/10	17/10.5
	Moisture Removal Pt./hr	4.1	5.1	5.1	6.8	11.0	5.1	6.3	11.0
<b>Heating</b>	Rated Heating Capacity Btu/hr	27,000	37,000	26,500	37,500	52,000	27,300	36,500	49,000
	COP 47°F	3.2	3.2	3.2	3.2	3.2	3.2	3.2	3.2
	Heating Capacity Range Btu/hr	6,800 - 34,100	8,500 - 41,000	6,800 - 34,100	8,500 - 41,000	13,600 - 64,800	6,800 - 30,500	8,500 - 38,500	13,600 - 61,000
<b>Outdoor Unit</b>	HSPF	10.0	10.0	11.0	10.5	10.0	10.0	10.3	10.5
	Maximum Fuse Size A	25	30	25	30	40	25	30	40
	Minimum Circuit Amp A	21	26	21	26	35	21	26	35
	Outdoor Noise Level dB	47	52	47	52	53	47	52	53
	Dimension: Height in (mm)	38 (965)	38 (965)	38 (965)	38 (965)	53 1/8 (1350)	38 (965)	38 (965)	53 1/8 (1350)
	Dimension: Width in (mm)	37 3/8 (950)	37 3/8 (950)	37 3/8 (950)	37 3/8 (950)	37 3/8 (950)	37 3/8 (950)	37 3/8 (950)	37 3/8 (950)
	Dimension: Depth in (mm)	14 5/8 (370)	14 5/8 (370)	14 5/8 (370)	14 5/8 (370)	14 5/8 (370)	14 5/8 (370)	14 5/8 (370)	14 5/8 (370)
Weight Ship/Net - lbs (kg)	202.8/ 176.4 (92/80)	207.2/180.7 (94/82)	202.8/ 176.4 (92/80)	207.2/180.7 (94/82)	260.1/231.5 (118/105)	202.8/ 176.4 (92/80)	207.2/180.7 (94/82)	260.1/231.5 (118/105)	
<b>Indoor Unit</b>	Indoor Sound dB (Turbo/High/Med/Low/Quiet)	49/47/42/36/34	50/48/44/38/36	40/38/35/32/29	34/32/28/25/23	42/41/36/33/31	38/36/33/29/26	47/45/42/38/34	42/41/36/33/31
	Airflow CFM (Turbo/High/Med/Low/Quiet)	710/650/560/440/410	720/660/570/450/420	950/950/860/760/700	1000/980/900/840/790	1210/1180/1070/990/940	600/550/430/360/310	700/650/550/450/400	800/750/650/550/450
	Dimension: Height in (mm)	13 1/4 (336)	14 3/8 (365)	9 7/8 (250)	9 7/8 (250)	9 7/8 (250)	9 5/8 (246)	9 5/8 (246)	11 3/8 (288)
	Dimension: Width in (mm)	43 7/8 (1115)	51 13/16 (1316)	37 5/8 (957)	59 (1500)	59 (1500)	33 1/8 (840)	33 1/8 (840)	33 1/8 (840)
	Dimension: Depth in (mm)	99/16 (243)	10 7/8 (275)	25 3/4 (655)	28 3/8 (720)	28 3/8 (720)	33 1/8 (840)	33 1/8 (840)	33 1/8 (840)
	Max. Ext. Static in.W.G (Pa)	NA	NA	0.6(150)	0.6(150)	0.6(150)	NA	NA	NA
	Drainpipe Size O.D. in	NA	NA	1 1/4	1 1/4	1 1/4	1	1	1
	Internal Condensate Pump	NA	NA	Standard	Standard	Standard	Standard	Standard	Standard
	Max. Drain-Lift in (mm)	NA	NA	27 9/16 (700)	27 9/16 (700)	27 9/16 (700)	39 3/8 (1000)	39 3/8 (1000)	39 3/8 (1000)
	Grille Model	NA	NA	NA	NA	NA	PB-950KB	PB-950KB	PB-950KB
	Grille Size: H×W×D in (mm)	NA	NA	NA	NA	NA	2 × 37 3/8 × 37 3/8 (50×950×950)	2 × 37 3/8 × 37 3/8 (50×950×950)	2 × 37 3/8 × 37 3/8 (50×950×950)
	Weight Ship/Net - lbs (kg)	45.4/37.5 (20.6/17)	55.1/46.3 (25.5/21)	81.1/68.8 (36.8/31.2)	130.1/121.3 (59/55)	132.3/114.6 (60/52)	79.4/68.3 (36/31)	79.4/68.3 (36/31)	83.8/70.5 (38/32)
	<b>Refrigerant Lines</b>	Connections	Flare	Flare	Flare	Flare	Flare	Flare	Flare
Liquid/Suction O.D. in		3/8 5/8	3/8 5/8	3/8 5/8	3/8 5/8	3/8 5/8	3/8 5/8	3/8 5/8	3/8 5/8
Factory Charge Oz		88	88	88	88	131	88	88	131
Maximum Line Length Ft / m		165/50	165/50	165/50	165/50	230/75	165/50	165/50	230/75
Maximum Height Ft / m		100/30	100/30	100/30	100/30	100/30	100/30	100/30	100/30



**GE APPLIANCES**  
a Haier company

Pub No. 26-H2205 Rev. 05-16-22.

©Copyright 2022 GE Appliances, a Haier Company. Our continued commitment to quality products may mean a change in specifications without notice.