



STANDARD PLAIN & PLASTIC RISER CLAMPS



Designed for supporting and stabilizing vertical pipe

- Maximum temperature Plain 650° F, Galvanized 450° F
- Designed for standard iron pipe
- Underwriters Laboratories Listed (UL) and Factory Mutual Approved (FM)
- Complies with Federal Specifications A-A-1192A Type 8, Manufacturers Standardization Society (MSS) ANSI/SP-69 and SP-58 Type 8

Sizes: 1/2" - 14"

Material: Carbon Steel

Finish: Plain & Plastic Coated

Approvals: UL, FM, Complies with A-A-1192A Type 8, ANSI/SP-69 & SP-58 Type 8

SIZE INCHES	ITEM PLAIN BLACK	ITEM PLASTIC COATED	MAX LOAD	WEIGHT LBS	A LENGTH	B WIDTH	C DISTANCE	D SPACE	BOLT SIZE	TORQUE VALUES	INNER BOX	MASTER BOX	PALLET QTY
1/2"	CLRS-PL12	CLRS-P12	220	0.8	8-1/2	1	2-5/16	3/8	3/8	19	10	50	2400
3/4"	CLRS-PL34	CLRS-P34	220	0.8	8-15/16	1	2-11/16	3/8	3/8	19	10	50	2400
1"	CLRS-PL01	CLRS-P01	220	1.04	8-15/16	1	2-51/64	3/8	3/8	19	10	50	2400
1-1/4"	CLRS-PL114	CLRS-P114	250	1.06	9-29/64	1	3-17/64	3/8	3/8	19	10	50	2400
1-1/2"	CLRS-PL112	CLRS-P112	250	1.08	9-7/8	1	3-49/64	3/8	3/8	19	10	50	2400
2"	CLRS-PL02	CLRS-P02	300	1.16	10-1/4	1-3/16	4-11/64	1/2	3/8	19	-	25	1200
2-1/2"	CLRS-PL212	CLRS-P212	400	1.32	11-1/64	1-3/16	4-7/8	1/2	3/8	19	-	25	1200
3"	CLRS-PL03	CLRS-P03	500	1.56	11-3/4	1-3/16	5-1/2	1/2	3/8	19	-	25	1200
3-1/2"	CLRS-PL312	-	600	1.7	12-41/64	1-3/16	6-1/2	1/2	3/8	19	-	20	720
4"	CLRS-PL04	CLRS-P04	750	1.7	13	1-3/16	6-39/64	1/2	1/2	50	-	20	720
5"	CLRS-PL05	CLRS-P05	1500	3.45	14-31/64	2	8-17/64	1/2	1/2	50	-	15	540
6"	CLRS-PL06	CLRS-P06	1600	3.7	15-63/64	2	9-39/64	1/2	1/2	50	-	10	360
8"	CLRS-PL08	CLRS-P08	2500	7.4	18-1/4	2	12-15/64	5/8	5/8	50	-	5	120
10"	CLRS-PL010	-	2500	11	20-5/8	2	14-39/64	5/8	5/8	65	-	-	120
12"	CLRS-PL012	-	2700	16.25	22-57/64	2	17-1/8	5/8	5/8	65	-	-	100
14"	CLRS-PL014	-	2700	17	24-31/64	2	18-17/64	5/8	5/8	65	-	-	60