

MAXIMUM OFFSET FOR MISALIGNED PIPES	0.25"
MAXIMUM OUT OF ROUNDNESS	1.5"-3" 4"- 12" 0.12" 0.16"
WORKING PRESSURE	1.5" - 12" 232 PSI
RATED PRESSURE	1.5" - 12" 350 PSI
VACUUM TEST	12 PSI

PRODUCT TABLES

HYMAX GRIP NOMINAL SIZE 1.5"-3"

Krausz Part Number	Nominal Diameter (inch)	Overall Range (inch)	Before removal of the inner layer (inch)	After removal of the inner layer (inch)	Bolts Num. and Size (mm)	Torque (Ft-Lbs)	Working Pressure (PSI)	Rated Pressure (PSI)	Approx. Weight (Lbs)
890-56-015039-16	1.5"/2"	1.54-2.64	1.54-2.20	2.17-2.64	2 - M14	70	232	350	15.45
890-56-025059-16	2.5"	2.32-3.43	2.32-2.99	2.95-3.43	2 - M14	70	232	350	20.26
890-56-030080-16	3"	3.15-4.17	3.15-3.74	3.70-4.17	2 - M14	70	232	350	25.53

HYMAX GRIP NOMINAL SIZE 4"-12"

Krausz Part Number	Nominal Diameter (inch)	Overall Range (inch)	Bolts Num. and Size (inch)	Torque (Ft-Lbs)	Working Pressure (PSI)	Rated Pressure (PSI)	Approx. Weight (Lbs)
890-56-04111-16	4"	4.40-5.10	2 - 5/8	90	232	350	32
890-56-06165-16	6"	6.50-7.20	2 - 5/8	110	232	350	43
890-56-08216-16	8"	8.50-9.40	2 - 3/4	200	232	350	74
890-56-10270-16	10"	10.65-11.55	2 - 3/4	200	232	350	92
890-56-12322-16	12"	12.68-13.39	2 - 3/4	200	232	350	100