

F1960 PEX BALL VALVES



600F Series F1960 Pex Ball Valve

CSA Certified • Lead Free • Full Port • 600 WOG



- Dezincification Resistant (DZR) Lead Free Brass Material
- Blow Out Proof Stem Design
- Stainless Steel Ball
- Vinyl Grip Lever Handle
- Expansion Pex Ends Conform to ASTM F1960
- Conforms to NSF/ANSI-61, NSF/ANSI-372, NSF/ANSI-14
- 400 psi WOG 150 psi WSP Service
- Temperature Range : -20°F to 300°F




PART #	SIZE	DESCRIPTION	INNER	MASTER
600F012-NL	1/2"	F1960 Pex Ball Valve	10	100
600F034-NL	3/4"	F1960 Pex Ball Valve	10	100
600F001-NL	1"	F1960 Pex Ball Valve	10	100
600F112-NL	1-1/2"	F1960 Pex Ball Valve	10	100
600F134-NL	1-3/4"	F1960 Pex Ball Valve	10	100
600F002-NL	2"	F1960 Pex Ball Valve	10	100

615F Series F1960 Pex T-Handle Ball Valve

CSA Certified • Lead Free • Full Port • 600 WOG



- Dezincification Resistant (DZR) Lead Free Brass Material
- Blow Out Proof Stem Design
- Stainless Steel Ball
- Vinyl Grip T-Handle
- Expansion Pex Ends Conform to ASTM F1960
- Conforms to NSF/ANSI-61, NSF/ANSI-372, NSF/ANSI-14
- 400 psi WOG 150 psi WSP Service
- Temperature Range : -20°F to 300°F



PART #	SIZE	DESCRIPTION	INNER	MASTER
615F012-NL	1/2"	F1960 Pex t-Handle Ball Valve	10	100
615F034-NL	3/4"	F1960 Pex t-Handle Ball Valve	10	100
615F001-NL	1"	F1960 Pex t-Handle Ball Valve	10	100

405 Series F1960 Pex Ball Valve w/ Drain

Purge Drain • CSA Certified • Lead Free • Full Port • 600 WOG



- Dezincification Resistant (DZR) Lead Free Brass Material
- Blow Out Proof Stem Design
- Stainless Steel Ball
- Vinyl Grip Lever Handle
- Expansion Pex Ends Conform to ASTM F1960
- Conforms to NSF/ANSI-61, NSF/ANSI-372, NSF/ANSI-14
- 400 psi WOG 150 psi WSP Service
- Temperature Range : -20°F to 300°F



PART #	SIZE	DESCRIPTION	INNER	MASTER
405F012-NL	1/2"	F1960 Pex Ball Valve	10	100
405F034-NL	3/4"	F1960 Pex Ball Valve	10	100
405F001-NL	1"	F1960 Pex Ball Valve	10	100