

FULL PORT • SWEAT ENDS • HIGH FLOW DRAIN • REVERSIBLE HANDLE • LEAD FREE

Features

- Forged brass body
- Blow-out proof stem design
- Reversible handle
- Easy system cleaning and flush
- Individually controlled drain outlets
- Valves with the 3-Way adjustable flow path

Specifications & Approvals

600 psi (WOG) 150 psi (WSP) Service
 Temperature Range: -20°F to 300°F

- Sweat end conforms to ASME B16.22
- NH Thread conforms to ANSI B1.20.7



Dimensions

Part#	Size	D1	D2	A	B	H	L
706C034-NL	3/4"	0.748	0.52	2.79	2.91	2.87	4.84
706C001-NL	1"	0.984	0.52	3.32	2.93	3.03	4.84

Material Specifications

Part Name	Material
1. Cap	Lead Free Brass
2. Seat	PTFE
3. Ball	Lead Free Brass
4. O-Ring	EPDM
5. Packing Nut	Brass
6. Stem	Brass
7. Lock Washer	Ferrum/Zinc Plated
8. Lock Nut	Ferrum/Zinc Plated
9. Packing	PTFE
10. Handle	Ferrum/Chrome Plated
11. Body	Lead Free Brass
12. O-Ring	NBR
13. Spring Washer	Ferrum/Zinc Plated
14. Screw	Ferrum/Zinc Plated
15. Handle	Al-alloy
16. Stem	Brass
17. O-Ring	EPDM
18. Seat	PTFE
19. Ball	Lead Free Brass
20. Seat	PTFE
21. Chain	PVC
22. Cap	Brass
23. Rubber Washer	EPDM
24. Cap	Lead Free Brass

