

## 200 CWP • THREAD • LEAD FREE

**Lead Free Brass Check Valves** feature a lead free cast brass body with NPT female threaded connections. They feature a brass body construction for longer life. These silent check valves have a low pressure drop and can be installed in a horizontal or vertical position.

### Features

- Lead free
- Cast brass body
- Thread ends conform to ANSI B2.1
- In-line check valve-spring loaded

### Specifications & Approvals

Max Pressure Rating: 200 psi CWP non shock  
 Temperature Range: 180°F  
 Conforms to NSF/ANSI-61/372



### Dimensions

Part#	Size	H	D
150T012-NL	1/2"	61	32
150T034-NL	3/4"	69.5	38
150T001-NL	1"	82	45
150T114-NL	1-1/4"	92	54
150T112-NL	1-1/2"	102.5	60
150T002-NL	2"	128	77

### Material Specifications

Part Name	Material
Stem Nut	Stainless Steel (304) Brass (C26000)
Spring Holder	Stainless Steel (304)
Spring	Stainless Steel (304)
Bonnet	Brass (C46400 MOD)
Body	Brass (C46400 MOD)
Stem House	POM M90 Formocon FM090 CF 500 P
O-Ring	Rubber (NBR) SN-719F
Stem	Brass (C46400 MOD)

