

FULL PORT • PRESS ENDS • HIGH FLOW DRAIN • REVERSIBLE HANDLE • LEAD FREE

Features

- Forged brass body
- Blow-out proof stem design
- Reversible handle
- Easy system cleaning and flush
- Individually controlled drain outlets
- Valves with the 3-Way adjustable flow path

Specifications & Approvals

600 psi (WOG) 150 psi (WSP) Service
Temperature Range: -20°F to 300°F

- Press end conforms to IAPMO PS117
- NH Thread conforms to ANSI B1.20.7



RAVEN
SPECIALTY PRODUCTS

Dimensions

Part#	Size	D1	D2	H	W1	W2	L
706R034-NL	3/4"	19	13.2	73.2	90	69.3	123
706R001-NL	1"	25	13.2	77.2	96	69.8	123
706R114-NL	1-1/4"	32	13.2	76.2	112	76.3	130
706R112-NL	1-1/2"	40	19	81.2	136	89.3	130
706R002-NL	2"	49.5	19	89.2	166	97	130

Material Specifications

Part Name	Material
1. Cap	Lead Free Brass
2. Seat	PTFE
3. Ball	Lead Free Brass
4. O-Ring	EPDM
5. Packing Nut	Brass
6. Stem	Brass
7. Lock Washer	Ferrum/Zinc Plated
8. Lock Nut	Ferrum/Zinc Plated
9. Packing	PTFE
10. Handle	Ferrum/Chrome Plated
11. Body	Lead Free Brass
12. O-Ring	NBR
13. Spring Washer	Ferrum/Zinc Plated
14. Screw	Ferrum/Zinc Plated
15. Handle	Al-alloy
16. Stem	Brass
17. O-Ring	EPDM
18. Seat	PTFE
19. Ball	Lead Free Brass
20. Seat	PTFE
21. Chain	PVC
22. Cap	Brass
23. Rubber Washer	EPDM
24. Cap	Lead Free Brass
25. O-Ring	EPDM

